

# CYLINDER VAPORIZATION RATE

Maximum Continuous Draw in BTU per Hour  
At Various Temperatures in Degree F

## FULL CYLINDERS

**LBS. of Propane in Cylinder**

Temperature (F)	40	30	20
0 F	55,000	45,000	36,000
20 F	79,000	66,000	51,000
40 F	105,000	85,000	68,000
60 F	131,000	107,000	83,000
70 F	141,000	118,000	92,000

## CYLINDERS AT 25%

**LBS. of Propane in Cylinder**

Temperature (F)	40	30	20
0 F	12,000	10,000	7,500
20 F	21,800	17,300	13,000
40 F	31,000	24,700	18,450
60 F	45,000	32,000	24,000
70 F	50,425	35,850	26,700

This manual has been provided courtesy of  
My RV Works, Inc.

[www.myrvworks.com](http://www.myrvworks.com)



You can find more RV service manuals here:

[www.myrvworks.com/manuals](http://www.myrvworks.com/manuals)

Over the years of running a mobile RV repair service, having a dedicated place to access service manuals for all the different appliances and components found on RVs was something that I always had a desire to create.

I hope this resource makes your RV repairs easier, as it has mine, but please be careful and follow proper safety practices when attempting to repair your own RV.

If in doubt, please consult with a professional RV technician!



DARREN KOEPP - OWNER, MY RV WORKS, INC.

*All service manuals provided on [www.myrvworks.com](http://www.myrvworks.com) are believed to be released for distribution and/or in the public domain.*