

Steps for Replacing E-Plex Control System Clock Module

1. Push bezel from right to left and pry out on left hand edge to remove.
2. Remove screws and remove clock module.
3. Remove wires from old clock module and connect new clock module.
4. Reinstall new clock module (~~three~~² screws).
5. Press tank button once to activate tank screen.
6. Press and hold tank button with blunt end of pen for 10 -15 seconds until module goes into programming mode.
7. Press down arrow button marked "stp".
8. Press down arrow button marked "all".
9. Press down arrow button marked "yes"
 - a. Reprogramming will cycle through all modules automatically
 - b. When complete, screen shows – Streaming: Inactive
10. Press up arrow button marked "str".
 - a. Screen goes to T-stat mode

NOTE: After replacing any module: tank sensor, temp sensor, etc., begin with Step #5.

Look for ~~⊖~~ ^{Write down} ~~⊖~~ ^{Address Timeouts}

This manual has been provided courtesy of
My RV Works, Inc.

www.myrvworks.com



You can find more RV service manuals here:

www.myrvworks.com/manuals

Over the years of running a mobile RV repair service, having a dedicated place to access service manuals for all the different appliances and components found on RVs was something that I always had a desire to create.

I hope this resource makes your RV repairs easier, as it has mine, but please be careful and follow proper safety practices when attempting to repair your own RV.

If in doubt, please consult with a professional RV technician!



DARREN KOEPP - OWNER, MY RV WORKS, INC.

All service manuals provided on www.myrvworks.com are believed to be released for distribution and/or in the public domain.